

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

SECTION 1. IDENTIFICATION

Product name : Dichlofenthion Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 3
Acute toxicity (Oral) : Category 4
Skin corrosion : Sub-category 1B
Serious eye damage : Category 1
Skin sensitization : Category 1
Germ cell mutagenicity : Category 2
Carcinogenicity (Oral) : Category 1A
Reproductive toxicity : Category 2
Specific target organ toxicity : Category 1 (Nervous system)
- single exposure
Specific target organ toxicity : Category 1 (Nervous system)
- repeated exposure
Specific target organ toxicity : Category 2 (Central nervous system, Kidney, Liver, Respiratory
- repeated exposure Tract, Auditory system)
Aspiration hazard : Category 1

Other hazards

Vapors may form explosive mixture with air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

GHS label elements

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H226 Flammable liquid and vapor. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H341 Suspected of causing genetic defects. H350 May cause cancer if swallowed. H361d Suspected of damaging the unborn child. H370 Causes damage to organs (Nervous system). H372 Causes damage to organs (Nervous system) through prolonged or repeated exposure. H373 May cause damage to organs (Central nervous system, Kidney, Liver, Respiratory Tract, Auditory system) through prolonged or repeated exposure.
Supplemental Hazard Statements	:	Corrosive to the respiratory tract.
Precautionary Statements	:	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking. P233 Keep container tightly closed. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe vapors. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves, protective clothing, eye protection and face protection. Response: P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER. P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

P308 + P313 IF exposed or concerned: Get medical attention.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Tar, wood	91722-33-7*	>= 10 - <= 30	TSC
Rosin	8050-09-7*	>= 10 - <= 30	TSC
Castor oil	8001-79-4*	>= 7 - <= 13	TSC
Tar, coal	8007-45-2*	>= 7 - <= 13	TSC
Ethylbenzene	100-41-4*	>= 7 - <= 13	TSC
Xylene	1330-20-7*	>= 7 - <= 13	TSC
Dichlofenthion (ISO)	97-17-6*	>= 1 - <= 5	TSC
Sodium hydroxide	1310-73-2*	>= 1 - <= 5	TSC
Phenol	108-95-2*	>= 1 - <= 5	TSC
m-Cresol	108-39-4*	>= 0.5 - <= 1.5	TSC
p-Cresol	106-44-5*	>= 0.5 - <= 1.5	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
Suspected of causing genetic defects.
May cause cancer if swallowed.
Suspected of damaging the unborn child.
Causes damage to organs.
Causes damage to organs through prolonged or repeated exposure.
Causes severe burns.
Corrosive to the respiratory tract.
Causes digestive tract burns.
No information available.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	1552594-00018	Date of first issue: 04/14/2017

- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NOx)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	1552594-00018	Date of first issue: 04/14/2017

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
 Date of first issue: 04/14/2017

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Rosin	8050-09-7	TWA (Inhalable particulate matter)	0.001 mg/m ³ (total Resin acids)	ACGIH
Castor oil	8001-79-4	TWA (mist - total)	10 mg/m ³	NIOSH REL
		TWA (mist - respirable)	5 mg/m ³	NIOSH REL
Tar, coal	8007-45-2	PEL	0.15 mg/m ³	OSHA CARC
		TWA	0.2 mg/m ³	NIOSH REL
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL
		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	20 ppm	ACGIH
Dichlofenthion (ISO)	97-17-6	TWA	20 µg/m ³ (OEB 3)	Internal
		Further information: Skin		
		Wipe limit	200 µg/100 cm ²	Internal
Sodium hydroxide	1310-73-2	C	2 mg/m ³	ACGIH
		C	2 mg/m ³	NIOSH REL
		TWA	2 mg/m ³	OSHA Z-1
Phenol	108-95-2	TWA	5 ppm	ACGIH
		TWA	5 ppm 19 mg/m ³	NIOSH REL
		C	15.6 ppm 60 mg/m ³	NIOSH REL
		TWA	5 ppm 19 mg/m ³	OSHA Z-1
m-Cresol	108-39-4	TWA	2.3 ppm 10 mg/m ³	NIOSH REL
		TWA	5 ppm 22 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction and vapor)	20 mg/m ³	ACGIH
p-Cresol	106-44-5	TWA	2.3 ppm 10 mg/m ³	NIOSH REL
		TWA	5 ppm 22 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction and vapor)	20 mg/m ³	ACGIH

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Phenol	108-95-2	Phenol	Urine	End of shift (As soon as possible after exposure ceases)	250 mg/g creatinine	ACGIH BEI
Tar, coal	8007-45-2	1-Hydroxypyrene	Urine	End of shift at end of work-week	2.5 µg/l	ACGIH BEI
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI

Engineering measures

- : Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections). All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment. Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face containment devices). Minimize open handling.
- Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving. Take note that the product is flammable, which may impact the selection of hand protection.

Eye protection : Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : dark, brown

Odor : strong

Odor Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : 86 °F / 30 °C

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	1552594-00018	Date of first issue: 04/14/2017

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	1,009 - 1,051 g/cm ³ (68 °F / 20 °C)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	1552594-00018	Date of first issue: 04/14/2017

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,450 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

|| Acute dermal toxicity : Acute toxicity estimate: 4,274 mg/kg
Method: Calculation method

Components:

Tar, wood:

|| Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Rosin:

|| Acute oral toxicity : LD50 (Rat): 2,800 mg/kg
|| Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Castor oil:

|| Acute oral toxicity : LD50 (Rat): > 4,763 mg/kg
Method: OECD Test Guideline 401
|| Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Tar, coal:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Acute oral toxicity : LD50 (Rat): 1,700 mg/kg
Acute inhalation toxicity :
Assessment: Not corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Dichlofenthion (ISO):

Acute oral toxicity : LD50 (Rat): 172 mg/kg

LD50 (Rat): 270 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.75 mg/l

Acute dermal toxicity : LD50 (Rat): 355 mg/kg

LD50 (Rabbit): 6,000 mg/kg

Sodium hydroxide:

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Phenol:

Acute oral toxicity : LD50 (Rat): 68 mg/kg
Method: OECD Test Guideline 401
Remarks: The test was conducted equivalent or similar to guideline

Acute toxicity estimate (Humans): 140 - 290 mg/kg
Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate (Rat): > 0.5 - 1 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit, female): 660 mg/kg
Method: OECD Test Guideline 402
Remarks: The test was conducted equivalent or similar to guideline

m-Cresol:

Acute oral toxicity : LD50 (Rat): 121 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 301 mg/kg
Remarks: Based on data from similar materials

p-Cresol:

Acute oral toxicity : LD50 (Rat): 172 - 250 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 213 - 426 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

Tar, wood:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Result : Skin irritation

Rosin:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Castor oil:

Species : Rabbit
Result : No skin irritation

Tar, coal:

Species : Rabbit

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

||Result : Mild skin irritation

Xylene:

||Species : Rabbit
||Result : Skin irritation

Dichlofenthion (ISO):

||Result : Mild skin irritation
||Remarks : Based on data from similar materials

Sodium hydroxide:

||Result : Corrosive after 3 minutes or less of exposure

Phenol:

||Result : Corrosive after 3 minutes to 1 hour of exposure
||Remarks : Based on national or regional regulation.

m-Cresol:

||Species : Rabbit
||Result : Corrosive after 3 minutes to 1 hour of exposure

p-Cresol:

||Species : Rabbit
||Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

|| Causes serious eye damage.

Components:

Tar, wood:

||Result : Irritation to eyes, reversing within 7 days

Rosin:

||Species : Rabbit
||Result : No eye irritation
||Method : OECD Test Guideline 405

Castor oil:

||Species : Rabbit
||Result : No eye irritation

Tar, coal:

||Species : Human
||Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Sodium hydroxide:

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

Phenol:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405
Remarks : The test was conducted equivalent or similar to guideline

m-Cresol:

Species : Rabbit
Result : Irreversible effects on the eye

p-Cresol:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Tar, wood:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitization rate in humans

Rosin:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Castor oil:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Tar, coal:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

Xylene:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative

Dichlofenthion (ISO):

Routes of exposure : Dermal
Assessment : Does not cause skin sensitization.
Result : Weak sensitizer
Remarks : Based on data from similar materials

Sodium hydroxide:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Result : negative

Phenol:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted equivalent or similar to guideline

p-Cresol:

Test Type : Draize Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Germ cell mutagenicity

|| Suspected of causing genetic defects.

Components:

Tar, wood:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Rosin:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Castor oil:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Tar, coal:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive
Remarks: Based on data from similar materials

Germ cell mutagenicity -
Assessment : Positive result(s) from in vivo mammalian somatic cell geno-
toxicity tests, supported by positive results from in vitro muta-
genicity assays.
Remarks: Based on national or regional regulation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Phenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted according to guideline

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: positive
Remarks: The test was conducted equivalent or similar to
guideline

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

	Remarks: The test was conducted equivalent or similar to guideline
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: positive Remarks: The test was conducted equivalent or similar to guideline
	Test Type: Transgenic rodent somatic cell gene mutation assay Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 488 Result: negative Remarks: The test was conducted according to guideline
Germ cell mutagenicity - Assessment	: Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

m-Cresol:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: positive
	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 475 Result: negative

p-Cresol:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: positive
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 478

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

||| Result: negative

Carcinogenicity

||| May cause cancer if swallowed.

Components:

Tar, coal:

||| Species : Mouse
||| Application Route : Ingestion
||| Exposure time : 2 Years
||| Result : positive

||| Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (oral)
Remarks: Based on national or regional regulation.

Ethylbenzene:

||| Species : Rat
||| Application Route : inhalation (vapor)
||| Exposure time : 104 weeks
||| Result : positive
||| Remarks : The mechanism or mode of action may not be relevant in humans.

Xylene:

||| Species : Rat
||| Application Route : Ingestion
||| Exposure time : 103 weeks
||| Result : negative

Phenol:

||| Species : Rat
||| Application Route : Ingestion
||| Exposure time : 103 weeks
||| Method : OECD Test Guideline 451
||| Result : negative
||| Remarks : The test was conducted equivalent or similar to guideline

||| Species : Mouse
||| Application Route : Ingestion
||| Exposure time : 103 weeks
||| Method : OECD Test Guideline 451
||| Result : negative
||| Remarks : The test was conducted equivalent or similar to guideline

m-Cresol:

||| Species : Mouse, males
||| Application Route : Ingestion
||| Exposure time : 105 weeks
||| Result : equivocal
||| Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Species : Mouse, female
Application Route : Ingestion
Exposure time : 106 - 107 weeks
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

p-Cresol:

Species : Mouse
Application Route : Ingestion
Exposure time : 106 - 107 weeks
Result : negative
Remarks : Based on data from similar materials

IARC	Group 1: Carcinogenic to humans	
	Tar, coal	8007-45-2
	Group 2B: Possibly carcinogenic to humans	
	Ethylbenzene	100-41-4
OSHA	OSHA specifically regulated carcinogen	
	Tar, coal (Coke oven emissions)	8007-45-2
NTP	Known to be human carcinogen	
	Tar, coal	8007-45-2

Reproductive toxicity

|| Suspected of damaging the unborn child.

Components:

Rosin:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Castor oil:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Application Route: Ingestion
Result: negative

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Dichlofenthion (ISO):

Effects on fetal development : Test Type: Development
Species: Mouse
Application Route: Intraperitoneal
Developmental Toxicity: LOAEL: 80 mg/kg body weight
Result: Reduced fetal weight., Embryotoxic effects.
Remarks: Based on data from similar materials

Test Type: Development
Species: Rat
Application Route: Intraperitoneal
Developmental Toxicity: LOAEL: 10 mg/kg body weight
Result: Reduced fetal weight., Embryotoxic effects., No teratogenic effects.
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Suspected of damaging the unborn child.

Phenol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Remarks: The test was conducted equivalent or similar to guideline

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

m-Cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat
Application Route: Ingestion
Result: negative

p-Cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

May cause respiratory irritation.
Causes damage to organs (Nervous system).
Corrosive to the respiratory tract.

Components:

Tar, coal:

Routes of exposure : Ingestion
Target Organs : Nervous system
Assessment : Shown to produce significant health effects in animals at concentrations of 300 mg/kg bw or less.

Xylene:

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

STOT-repeated exposure

Causes damage to organs (Nervous system) through prolonged or repeated exposure.
May cause damage to organs (Central nervous system, Kidney, Liver, Respiratory Tract, Auditory system) through prolonged or repeated exposure.

Components:

Tar, coal:

Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Ethylbenzene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Xylene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Dichlofenthion (ISO):

Target Organs : Nervous system
Assessment : Causes damage to organs through prolonged or repeated exposure.
Remarks : Based on human experience.

Phenol:

Target Organs : Central nervous system, Kidney, Liver
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Rosin:

Species : Rat, male
NOAEL : 335 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Castor oil:

Species : Rat
NOAEL : > 5,000 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Ethylbenzene:

Species : Rat
LOAEL : 0.868 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Dichlofenthion (ISO):

Species : Rat
NOAEL : 0.75 mg/kg
Application Route : Oral
Exposure time : 90 d

Species : Dog
NOAEL : 0.75 mg/kg
Application Route : Oral
Exposure time : 90 d

Phenol:

Species : Rat
LOAEL : > 10 - 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)
Exposure time : 90 Days

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

m-Cresol:

Species : Rat
NOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408

p-Cresol:

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 175 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Aspiration toxicity

|| May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:

Ethylbenzene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Dichlofenthion (ISO):

Skin contact : Symptoms: irritating, central nervous system effects, sweating
Remarks: Can be absorbed through skin.
May cause sensitization by skin contact.
Eye contact : Symptoms: constriction of pupils, central nervous system effects
Ingestion : Symptoms: Nausea, Diarrhea, Vomiting, sweating, Lachrymation, constriction of pupils, Central nervous system depression, Gastrointestinal disturbance, bronchospasm, central nervous system effects, Edema

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Tar, wood:

- | | | |
|---|---|---|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 28 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | EC50 (Desmodesmus subspicatus (green algae)): 17 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |
| | | EC10 (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |

Rosin:

- | | | |
|---|---|--|
| Toxicity to fish | : | LL50 (Danio rerio (zebra fish)): > 1 - 10 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials |
| Toxicity to daphnia and other aquatic invertebrates | : | EL50 (Daphnia magna (Water flea)): 911 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | EL50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201 |
| | | NOELR (Raphidocelis subcapitata (freshwater green alga)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201 |
| Toxicity to microorganisms | : | EC50 (activated sludge): > 10,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209 |

Castor oil:

- | | | |
|------------------|---|---|
| Toxicity to fish | : | LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: ISO 7346/1
Remarks: Based on data from similar materials |
|------------------|---|---|

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): 54,000 mg/l
Exposure time: 30 min

Tar, coal:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 250 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 2.8 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): 36 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Desmodesmus subspicatus (green algae)): 5 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l Exposure time: 96 h NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l Exposure time: 7 d
Toxicity to microorganisms	:	EC50 (Nitrosomonas sp.): 96 mg/l Exposure time: 24 h

Xylene:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 24 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EC50 (Skeletonema costatum (marine diatom)): 10 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l Exposure time: 35 d Method: OECD Test Guideline 210 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	NOEC: > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: Based on data from similar materials

Dichlofenthion (ISO):

Toxicity to fish	:	LC50 (No species specified): 0.64 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.23 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	---	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.0011 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Phenol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.9 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50: 76 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 0.077 mg/l
Exposure time: 60 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.05 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: The test was conducted according to guideline

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 21 mg/l
Exposure time: 24 h

m-Cresol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.6 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): > 99.5 mg/l
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 1.35 mg/l
Exposure time: 32 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

p-Cresol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7.4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7.7 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 7.8 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

	EC10 (Desmodesmus subspicatus (green algae)): 2.3 mg/l Exposure time: 48 h
Toxicity to fish (Chronic toxicity)	: NOEC (Pimephales promelas (fathead minnow)): 1.35 mg/l Exposure time: 32 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1 mg/l Exposure time: 21 d
Toxicity to microorganisms	: IC50 (Nitrosomonas sp.): 260 mg/l Exposure time: 24 h

Persistence and degradability

Components:

Tar, wood:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 47 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	---

Rosin:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 71 % Exposure time: 28 d Method: OECD Test Guideline 301D
------------------	---

Castor oil:

Biodegradability	: Result: Readily biodegradable. Remarks: Based on data from similar materials
------------------	---

Ethylbenzene:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 70 - 80 % Exposure time: 28 d
------------------	--

Xylene:

Biodegradability	: Result: Readily biodegradable. Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials
------------------	--

Phenol:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 62 % Exposure time: 4 d Method: OECD Test Guideline 301C Remarks: The test was conducted according to guideline
------------------	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Biodegradation Simulation Tests : Environmental Compartment: Estuarine water
Value type: DT50
Value: 15 d

Environmental Compartment: Soil
Value type: DT50
Value: 7 d

m-Cresol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

p-Cresol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 8 d

Bioaccumulative potential

Components:

Tar, wood:

Partition coefficient: n-octanol/water : log Pow: 0.2 - 2.02

Rosin:

Partition coefficient: n-octanol/water : log Pow: > 3 - 6.2
Method: OECD Test Guideline 117

Castor oil:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Calculation

Tar, coal:

Partition coefficient: n-octanol/water : Remarks: No data available

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.6

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

Dichlofenthion (ISO):

Partition coefficient: n-octanol/water : log Pow: 5.14

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

|| octanol/water

Phenol:

|| Bioaccumulation : Species: Danio rerio (zebra fish)
Bioconcentration factor (BCF): 17.5
Method: OECD Test Guideline 305
Remarks: The test was conducted equivalent or similar to guideline

|| Partition coefficient: n-octanol/water : log Pow: 1.47

m-Cresol:

|| Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 17 - 20

|| Partition coefficient: n-octanol/water : log Pow: 1.96

p-Cresol:

|| Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 17 - 20
Remarks: Based on data from similar materials

|| Partition coefficient: n-octanol/water : log Pow: 1.94

Mobility in soil

Components:

Phenol:

|| Distribution among environmental compartments : log Koc: 1.15
Method: OECD Test Guideline 106
Remarks: The test was conducted according to guideline

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 2920
Proper shipping name : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Sodium hydroxide, Ethylbenzene)
Class : 8
Subsidiary risk : 3
Packing group : II
Labels : 8 (3)
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 2920
Proper shipping name : Corrosive liquid, flammable, n.o.s.
(Sodium hydroxide, Ethylbenzene)
Class : 8
Subsidiary risk : 3
Packing group : II
Labels : Corrosive, Flammable Liquids
Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851

IMDG-Code

UN number : UN 2920
Proper shipping name : CORROSIVE LIQUID, FLAMMABLE, N.O.S.
(Sodium hydroxide, Ethylbenzene, Dichlofenthion (ISO), Tar, wood)
Class : 8
Subsidiary risk : 3
Packing group : II
Labels : 8 (3)
EmS Code : F-E, S-C
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 2920
Proper shipping name : Corrosive liquids, flammable, n.o.s.
(Sodium hydroxide, Ethylbenzene)
Class : 8
Subsidiary risk : 3
Packing group : II
Labels : CORROSIVE, FLAMMABLE LIQUID
ERG Code : 132
Marine pollutant : yes(Dichlofenthion (ISO))

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 1552594-00018 Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Tar, coal	8007-45-2	1	8
Tar, coal	8007-45-2		8
Xylene	1330-20-7	100	1075
m-Cresol	108-39-4	100	9090

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Phenol	108-95-2	1000	52631

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)
Phenol	108-95-2	10000

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Ethylbenzene	100-41-4	>= 5 - < 10 %
Xylene	1330-20-7	>= 5 - < 10 %
Phenol	108-95-2	>= 1 - < 5 %
m-Cresol	108-39-4	>= 1 - < 5 %
p-Cresol	106-44-5	>= 1 - < 5 %

US State Regulations

Pennsylvania Right To Know

Tar, wood

91722-33-7

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	1552594-00018	Date of first issue: 04/14/2017

Rosin	8050-09-7
Castor oil	8001-79-4
Water	7732-18-5
Tar, coal	8007-45-2
Ethylbenzene	100-41-4
Xylene	1330-20-7
Dichlofenthion (ISO)	97-17-6
Sodium hydroxide	1310-73-2
Phenol	108-95-2
m-Cresol	108-39-4
p-Cresol	106-44-5

California Prop. 65

WARNING: This product can expose you to chemicals including Tar, coal, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Tar, coal	8007-45-2
Ethylbenzene	100-41-4
Xylene	1330-20-7
Sodium hydroxide	1310-73-2
Phenol	108-95-2
m-Cresol	108-39-4
p-Cresol	106-44-5

California Permissible Exposure Limits for Chemical Contaminants

Tar, coal	8007-45-2
Ethylbenzene	100-41-4
Xylene	1330-20-7
Sodium hydroxide	1310-73-2
Phenol	108-95-2
m-Cresol	108-39-4
p-Cresol	106-44-5

California Regulated Carcinogens

Tar, coal	8007-45-2
-----------	-----------

The ingredients of this product are reported in the following inventories:

AICS	: not determined
CA. DSL	: not determined
IECSC	: not determined

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation


Version
9.0

Revision Date:
12/06/2025

SDS Number:
1552594-00018

Date of last issue: 04/14/2025
Date of first issue: 04/14/2017

NFPA 704:



HMIS® IV:

HEALTH	*	4
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	1552594-00018	Date of first issue: 04/14/2017

50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/06/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8