

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

SECTION 1. IDENTIFICATION

Product name : Copper Oxide Solid Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Other hazards

Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.

Hazards associated with a change in physical form:

Conditions	Hazards
If small particles are generated during further processing, handling or by other means.	May form combustible dust concentrations in air.

GHS label elements

Hazard pictograms :

Signal Word : Warning

Hazard Statements : H351 Suspected of causing cancer.
H361d Suspected of damaging the unborn child.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Polyethylene glycol	25322-68-3*	>= 45 - <= 70	TSC
Copper oxide	1317-38-0*	>= 30 - <= 60	TSC
Calcium carbonate	471-34-1*	>= 3 - <= 7	TSC
Diiron trioxide	1309-37-1*	>= 0.5 - <= 1.5	TSC
tert-Butyl-4-methoxyphenol	25013-16-5*	>= 0.1 - <= 1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : If in eyes, rinse well with water.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 02/06/2026
8.0	02/20/2026	11153924-00014	Date of first issue: 12/20/2022

Most important symptoms and effects, both acute and delayed	:	Contact with dust can cause mechanical irritation or drying of the skin. Dust contact with the eyes can lead to mechanical irritation. No information available. Suspected of causing cancer. Suspected of damaging the unborn child.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Carbon oxides Metal oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dispersal of dust in the air (i.e., clearing dust surfaces

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not breathe dust.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Polyethylene glycol	25322-68-3	TWA (aerosol)	10 mg/m ³	US WEEL
Copper oxide	1317-38-0	TWA (Fumes)	0.1 mg/m ³ (Copper)	NIOSH REL
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

			bonate)	
Diiron trioxide	1309-37-1	TWA (Respirable particulate matter)	5 mg/m ³	ACGIH
		TWA (dust and fume)	5 mg/m ³ (Iron)	NIOSH REL
		TWA (Fumes)	10 mg/m ³	OSHA Z-1
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1

Engineering measures : Use feasible engineering controls to minimize exposure to compound.
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material

: Chemical-resistant gloves

Eye protection

: Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.
Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection
Hygiene measures

: Work uniform or laboratory coat.
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	capsule
Color	:	metallic gray
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	May form explosive dust-air mixture during processing, handling or other means.
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : May form explosive dust-air mixture during processing, handling or other means.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.
Avoid dust formation.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Polyethylene glycol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Copper oxide:

Acute oral toxicity : LD50 (Rat, male): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
Remarks: The test was conducted according to guideline

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The test was conducted according to guideline

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Diiron trioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): > 5.05 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

tert-Butyl-4-methoxyphenol:

Acute oral toxicity : LD50 (Rabbit): 2,100 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Polyethylene glycol:

Species : Rabbit
Method : OECD Test Guideline 404

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Result : No skin irritation
Remarks : Based on data from similar materials

Copper oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : The test was conducted according to guideline

Calcium carbonate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Diiron trioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

tert-Butyl-4-methoxyphenol:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Polyethylene glycol:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Copper oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The test was conducted according to guideline

Calcium carbonate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Diiron trioxide:

Species : Rabbit
Result : No eye irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Method : OECD Test Guideline 405

tert-Butyl-4-methoxyphenol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Polyethylene glycol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Copper oxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline

Calcium carbonate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

tert-Butyl-4-methoxyphenol:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Polyethylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Result: negative
Remarks: Based on data from similar materials

Copper oxide:

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: Regulation (EC) No. 440/2008, Annex, B.12
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Calcium carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Diiron trioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 489
Result: negative

tert-Butyl-4-methoxyphenol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Carcinogenicity

Suspected of causing cancer.

Components:

tert-Butyl-4-methoxyphenol:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks
Result : positive

Species : Hamster, male
Application Route : Ingestion
Exposure time : 24 weeks
Result : positive

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC Group 2B: Possibly carcinogenic to humans
tert-Butyl-4-methoxyphenol 25013-16-5
(butylated hydroxyanisole)
(BHA)

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Reasonably anticipated to be a human carcinogen
tert-Butyl-4-methoxyphenol 25013-16-5
(Butylated Hydroxyanisole)
(BHA)

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Copper oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

tert-Butyl-4-methoxyphenol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Fertility/early embryonic development
Species: Mouse
Application Route: Ingestion
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Calcium carbonate:

Species : Rat
NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 422

Diiron trioxide:

Species : Rat
NOAEL : >= 1,000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 02/06/2026
8.0	02/20/2026	11153924-00014	Date of first issue: 12/20/2022

tert-Butyl-4-methoxyphenol:

Species	:	Rat
NOAEL	:	50 mg/kg
LOAEL	:	250 mg/kg
Application Route	:	Ingestion
Exposure time	:	8 Months

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Polyethylene glycol:

Toxicity to fish	:	LC50 (Poecilia reticulata (guppy)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
------------------	---	---

Copper oxide:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 0.1 - 1 mg/l Exposure time: 96 h Remarks: Based on transformation/dissolution testing and data from soluble metal compounds
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 0.1 - 1 mg/l Exposure time: 48 h Remarks: Based on transformation/dissolution testing and data from soluble metal compounds
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOELR (Ceriodaphnia dubia (water flea)): > 0.1 - 1 mg/l Exposure time: 7 d Remarks: Based on transformation/dissolution testing and data from soluble metal compounds

Calcium carbonate:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic	:	NOELR (Pseudokirchneriella subcapitata (green algae)): 50

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

- plants mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- Toxicity to microorganisms : NOEC: 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
- Diiron trioxide:**
- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 20
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOELR (Raphidocelis subcapitata (freshwater green alga)):
>= 20 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other : NOELR (Daphnia magna (Water flea)): >= 20 mg/l
aquatic invertebrates (Chron-
ic toxicity) Exposure time: 21 d
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EL50 (activated sludge): >= 100 mg/l
Exposure time: 3 h
Method: ISO 8192
Remarks: Based on data from similar materials

tert-Butyl-4-methoxyphenol:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1.56 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.3 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 02/06/2026
8.0	02/20/2026	11153924-00014	Date of first issue: 12/20/2022

aquatic invertebrates	Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.9 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	NOEC (Pseudokirchneriella subcapitata (green algae)): 0.25 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Persistence and degradability

Components:

Polyethylene glycol:

Biodegradability	: Result: rapidly degradable Remarks: Based on data from similar materials
------------------	---

Bioaccumulative potential

Components:

Polyethylene glycol:

Partition coefficient: n-octanol/water	: log Pow: < 3
--	----------------

tert-Butyl-4-methoxyphenol:

Bioaccumulation	: Species: Oryzias latipes (Orange-red killifish) Bioconcentration factor (BCF): 16 - 21
-----------------	---

Partition coefficient: n-octanol/water	: log Pow: 2.82 Method: OECD Test Guideline 117
--	--

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

|| (Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
|| (Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

|| Remarks : This product can be subject to exemptions when packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids, or having a net mass of 5 kg or less for solids.

IMDG-Code

UN number : UN 3077
|| Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

|| Remarks : This product can be subject to exemptions when packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids, or having a net mass of 5 kg or less for solids.

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077
|| Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(Copper oxide, 2,6-Di-tert-butyl-p-cresol)
Remarks : Above applies only to containers over 119 gallons (450 liters) in case of liquids, or 882 lbs. (400 kg) in case of solids. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO. Above applies only to containers over 119 gallons (450 liters) in case of liquids, or 882 lbs. (400 kg) in case of solids.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity
Reproductive toxicity

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Copper oxide 1317-38-0 >= 30 - < 50 %

US State Regulations

Pennsylvania Right To Know

Polyethylene glycol	25322-68-3
Copper oxide	1317-38-0
Polyethylene Oxide	25372-68-3
Calcium carbonate	471-34-1
Diiron trioxide	1309-37-1

California Prop. 65

WARNING: This product can expose you to chemicals including tert-Butyl-4-methoxyphenol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Copper oxide 1317-38-0

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version 8.0 Revision Date: 02/20/2026 SDS Number: 11153924-00014 Date of last issue: 02/06/2026
Date of first issue: 12/20/2022

Diiron trioxide 1309-37-1

California Permissible Exposure Limits for Chemical Contaminants

Calcium carbonate 471-34-1
Diiron trioxide 1309-37-1


The ingredients of this product are reported in the following inventories:

AICS : not determined
CA. DSL : not determined
IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	0
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA : 8-hour time weighted average
US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Copper Oxide Solid Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 02/06/2026
8.0	02/20/2026	11153924-00014	Date of first issue: 12/20/2022

German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 02/20/2026

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8