

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

SECTION 1. IDENTIFICATION

Product name : MineralFix Formulation
Product code : ProteAQ MineralFix

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Serious eye damage : Category 1

Other hazards

Contact with dust can cause mechanical irritation or drying of the skin.

Hazards associated with a change in physical form:

Conditions	Hazards
If small particles are generated during further processing, handling or by other means.	May form combustible dust concentrations in air.

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

Supplemental Hazard Statements : Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**
P280 Wear eye protection and face protection.
Response:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025



P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Magnesium chloride	7786-30-3*	>= 10 - <= 30	TSC
Calcium chloride	10043-52-4*	>= 10 - <= 30	TSC
Silica gel, precipitated, crystalline free	112926-00-8*	>= 1 - <= 5	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap.
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye damage.
Corrosive to the respiratory tract.
Contact with dust can cause mechanical irritation or drying of the skin.
No information available.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2025
4.2	12/08/2025	11504106-00004	Date of first issue: 01/22/2025

- Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Metal oxides
Chlorine compounds
Sulfur oxides
Silicon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2025
4.2	12/08/2025	11504106-00004	Date of first issue: 01/22/2025

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. |
| Local/Total ventilation | : | Use only with adequate ventilation. |
| Advice on safe handling | : | Do not breathe dust.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers.
Keep tightly closed.
Store in accordance with the particular national regulations. |
| Materials to avoid | : | Do not store with the following product types:
Strong oxidizing agents |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust	50 Million particles per cubic foot Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	15 mg/m ³ Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	5 mg/m ³ Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
	15 Million particles per cubic foot Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
Dust, nuisance dust and particulates	10 mg/m ³ Value type (Form of exposure): PEL (Total dust) Basis: CAL PEL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

5 mg/m³
Value type (Form of exposure): PEL (respirable dust fraction)
Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Magnesium chloride	7786-30-3	TWA	OEB 2 (>= 100 < 1000 µg/m ³)	Internal
Silica gel, precipitated, crystalline free	112926-00-8	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Engineering measures : All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment. Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face containment devices). Minimize open handling.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.
Eye protection : Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

Hygiene measures : Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially contaminated clothing.
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : white, beige

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture during processing, handling or other means.

Flammability (liquids) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2025
4.2	12/08/2025	11504106-00004	Date of first issue: 01/22/2025

Density	:	No data available
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics	:	
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	May form explosive dust-air mixture during processing, handling or other means. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks. Avoid dust formation.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
---------------------	---	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

Components:

Magnesium chloride:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
Remarks: The test was conducted according to guideline
Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The test was conducted according to guideline
Based on data from similar materials

Calcium chloride:

Acute oral toxicity : LD50 (Rat): 2,120 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Silica gel, precipitated, crystalline free:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 0.69 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Magnesium chloride:

Species : reconstructed human epidermis (RhE)
Method : Regulation (EC) No. 440/2008, Annex, B.46
Remarks : The test was conducted equivalent or similar to guideline
Based on data from similar materials

Result : No skin irritation

Calcium chloride:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Silica gel, precipitated, crystalline free:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Magnesium chloride:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The test was conducted according to guideline
Based on data from similar materials

Calcium chloride:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Silica gel, precipitated, crystalline free:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Magnesium chloride:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline
Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

Germ cell mutagenicity

Not classified based on available information.

Components:

Magnesium chloride:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: The test was conducted according to guideline

Calcium chloride:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Silica gel, precipitated, crystalline free:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

Components:

Magnesium chloride:

Species : Mouse
Application Route : Ingestion
Exposure time : 96 weeks
Method : OECD Test Guideline 453
Result : negative
Remarks : The test was conducted equivalent or similar to guideline
Based on data from similar materials

Calcium chloride:

Species : Mouse
Application Route : Ingestion
Exposure time : 96 weeks
Result : negative
Remarks : Based on data from similar materials

Silica gel, precipitated, crystalline free:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Magnesium chloride:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted equivalent or similar to guideline
Based on data from similar materials

Calcium chloride:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Silica gel, precipitated, crystalline free:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Corrosive to the respiratory tract.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Magnesium chloride:

Species : Rat
NOAEL : 308 mg/kg
LOAEL : 1,600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

Silica gel, precipitated, crystalline free:

Species : Rat
NOAEL : > 4,500 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version 4.2 Revision Date: 12/08/2025 SDS Number: 11504106-00004 Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Magnesium chloride:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 2,119.3 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 548.4 mg/l
Exposure time: 48 h
Remarks: No test guideline followed |
| Toxicity to algae/aquatic plants | : | ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline

NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | EC10 (Daphnia magna (Water flea)): 321 mg/l
Exposure time: 21 d |
| Toxicity to microorganisms | : | NOEC (activated sludge): > 900 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: The test was conducted according to guideline |

Calcium chloride:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials |
| Toxicity to algae/aquatic plants | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials |

Silica gel, precipitated, crystalline free:

- | | | |
|------------------|---|--|
| Toxicity to fish | : | LL50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
|------------------|---|--|

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2025
4.2	12/08/2025	11504106-00004	Date of first issue: 01/22/2025

	Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EL50 (Scenedesmus subspicatus): > 10,000 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2025
4.2	12/08/2025	11504106-00004	Date of first issue: 01/22/2025

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Sodium chloride	7647-14-5
Zeolites	1318-02-1
Calcium chloride	10043-52-4
Magnesium chloride	7786-30-3
Potassium chloride	7447-40-7
Magnesium sulphate	7487-88-9
Silica gel, precipitated, crystalline free	112926-00-8

California Permissible Exposure Limits for Chemical Contaminants

Silica gel, precipitated, crystalline free	112926-00-8
--	-------------

The ingredients of this product are reported in the following inventories:

AICS : not determined

CA. DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation


Version
4.2

Revision Date:
12/08/2025

SDS Number:
11504106-00004

Date of last issue: 06/18/2025
Date of first issue: 01/22/2025

NFPA 704:



HMIS® IV:

HEALTH	/	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

CAL PEL	:	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



MineralFix Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06/18/2025
4.2	12/08/2025	11504106-00004	Date of first issue: 01/22/2025

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/08/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8