

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

SECTION 1. IDENTIFICATION

Product name : Metal Sulfates Formulation
Product code : Minebloom

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Serious eye damage : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 1B
Reproductive toxicity : Category 1B
Specific target organ toxicity : Category 1 (Brain)
- repeated exposure

Other hazards

None known.

Hazards associated with a change in physical form:

Conditions	Hazards
If small particles are generated during further processing, handling or by other means.	May form combustible dust concentrations in air.

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H302 + H332 Harmful if swallowed or if inhaled.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H350 May cause cancer.
H360FD May damage fertility. May damage the unborn child.
H372 Causes damage to organs (Brain) through prolonged or repeated exposure.

Supplemental Hazard Statements : Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.
P308 + P313 IF exposed or concerned: Get medical attention.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents and container to an approved waste

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Calcium bis(dihydrogenorthophosphate)	7758-23-8*	$\geq 10 - \leq 30$	TSC
Silicon dioxide	7631-86-9*	$\geq 3 - \leq 7$	TSC
Ethylene diamine tetraacetic acid	60-00-4*	$\geq 3 - \leq 7$	TSC
Sulfuric acid, iron(2+) salt (1:1), monohydrate	17375-41-6*	$\geq 1 - \leq 5$	TSC
Sodium molybdate (VI) dihydrate	10102-40-6*	$\geq 1 - \leq 5$	TSC
Disodium octaborate tetrahydrate	12280-03-4*	$\geq 1 - \leq 5$	TSC
Manganese sulfate	10034-96-5*	$\geq 1 - \leq 5$	TSC
Copper(II) sulfate, pentahydrate	7758-99-8*	$\geq 1 - \leq 5$	TSC
Zinc sulphate monohydrate	7446-19-7*	$\geq 0.5 - \leq 1.5$	TSC
Sodium selenite	10102-18-8*	$\geq 0.5 - \leq 1.5$	TSC
Cobalt Chloride	7646-79-9*	$\geq 0 - \leq 0.1$	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

If swallowed	:	for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention immediately. If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	Harmful if swallowed or if inhaled. May cause an allergic skin reaction. Causes serious eye damage. May cause cancer. May damage fertility. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure. Corrosive to the respiratory tract. No information available.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard. Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Metal oxides Sulfur oxides Oxides of phosphorus Chlorine compounds Carbon oxides Nitrogen oxides (NO _x)
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Surround spill with absorbents and place a damp covering over the area to minimize entry of the material into the air. Add excess liquid to allow the material to enter into solution. Soak up with inert absorbent material. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing. Do not breathe dust. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Keep container tightly closed. Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

- Conditions for safe storage : Take care to prevent spills, waste and minimize release to the environment.
: Keep in properly labeled containers.
: Store locked up.
: Keep tightly closed.
: Keep in a cool, well-ventilated place.
: Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
: Strong oxidizing agents
: Self-reactive substances and mixtures
: Organic peroxides
: Explosives
: Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

- inert or nuisance dust 50 Million particles per cubic foot
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3
- 15 mg/m³
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3
- 5 mg/m³
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3
- 15 Million particles per cubic foot
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3
- Dust, nuisance dust and particulates 10 mg/m³
Value type (Form of exposure): PEL (Total dust)
Basis: CAL PEL
- 5 mg/m³
Value type (Form of exposure): PEL (respirable dust fraction)
Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
 Date of first issue: 09/22/2025

			(Silica)	
Sulfuric acid, iron(2+) salt (1:1), monohydrate	17375-41-6	TWA	1 mg/m ³ (Iron)	ACGIH
		TWA	1 mg/m ³ (Iron)	NIOSH REL
Sodium molybdate (VI) dihydrate	10102-40-6	TWA	5 mg/m ³ (Molybdenum)	OSHA Z-1
		TWA (Respirable particulate matter)	0.5 mg/m ³ (Molybdenum)	ACGIH
Disodium octaborate tetrahydrate	12280-03-4	TWA (Inhalable particulate matter)	2 mg/m ³ (Borate)	ACGIH
		STEL (Inhalable particulate matter)	6 mg/m ³ (Borate)	ACGIH
Manganese sulfate	10034-96-5	C	5 mg/m ³ (Manganese)	OSHA Z-1
		TWA (Inhalable particulate matter)	0.1 mg/m ³ (Manganese)	ACGIH
		TWA (Respirable particulate matter)	0.02 mg/m ³ (Manganese)	ACGIH
		TWA	1 mg/m ³ (Manganese)	NIOSH REL
		ST	3 mg/m ³ (Manganese)	NIOSH REL
Copper(II) sulfate, pentahydrate	7758-99-8	TWA	1 mg/m ³ (Copper)	NIOSH REL
Sodium selenite	10102-18-8	TWA	20 µg/m ³ (OEB 3)	Internal
		Wipe limit	200 µg/100 cm ²	Internal
		TWA	0.2 mg/m ³ (selenium)	OSHA Z-1
		TWA	0.2 mg/m ³ (selenium)	ACGIH
		TWA	0.2 mg/m ³ (selenium)	NIOSH REL
Cobalt Chloride	7646-79-9	TWA (Inhalable particulate matter)	0.02 mg/m ³ (Cobalt)	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Cobalt Chloride	7646-79-9	Cobalt (Cobalt)	Urine	End of shift at end of work-	15 µg/l	ACGIH BEI

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

				week		
--	--	--	--	------	--	--

Engineering measures : The information below is intended for larger pilot/commercial-scale operations and manufacturing. For smaller scale, clinical, or pharmacy settings, site-specific internal risk assessment practices should be conducted to determine appropriate exposure control measures. The health hazard risks of handling this material are dependent on multiple factors, including but not limited to physical form and quantity handled. If applicable, use process enclosures, local exhaust ventilation (e.g., Biosafety Cabinet, Ventilated Balance Enclosures), or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels as low as reasonably achievable. Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., vacuum conveying from a closed system, packout head with inflatable seal from stationary container, ventilated enclosure, etc.). All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment. Essentially no open handling permitted. Use closed processing systems or containment technologies.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.
Eye protection : Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Hygiene measures : contaminated clothing.
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	No data available
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	May form explosive dust-air mixture during processing, handling or other means.
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics		
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	May form explosive dust-air mixture during processing, handling or other means. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks. Avoid dust formation.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 481.73 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 4.19 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Calcium bis(dihydrogenorthophosphate):

Acute oral toxicity : LD50 (Rat): 3,986 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5,110 mg/kg
Method: OECD Test Guideline 401
Remarks: The test was conducted according to guideline

Acute inhalation toxicity : LC50 (Rat): > 5.198 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: The test was conducted according to guideline

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No test guideline followed

Ethylene diamine tetraacetic acid:

Acute oral toxicity : LD50 (Rat): 4,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1 mg/l
Exposure time: 6 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 412
Remarks: Based on data from similar materials

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: The test was conducted according to guideline
Based on data from similar materials

Sodium molybdate (VI) dihydrate:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

- Acute oral toxicity : LD50 (Rat): 4,972 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 3.93 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Disodium octaborate tetrahydrate:

- Acute oral toxicity : LD50 (Rat): 2,550 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 2.01 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Manganese sulfate:

- Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Remarks: No test guideline followed
- Acute inhalation toxicity : LC50 (Rat): > 4.98 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: The test was conducted according to guideline

Copper(II) sulfate, pentahydrate:

- Acute oral toxicity : LD50 (Rat): 481 mg/kg
Method: OECD Test Guideline 401
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Zinc sulphate monohydrate:

- Acute oral toxicity : LD50 (Rat): > 1,000 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Sodium selenite:

Acute oral toxicity : LD50 (Rat): 4.8 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.052 - 0.51 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Cobalt Chloride:

Acute oral toxicity : LD50 (Rat): 537 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Calcium bis(dihydrogenorthophosphate):

Species : Rabbit
Result : No skin irritation

Silicon dioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : The test was conducted according to guideline

Ethylene diamine tetraacetic acid:

Species : Rabbit
Result : No skin irritation

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : The test was conducted according to guideline

Sodium molybdate (VI) dihydrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Disodium octaborate tetrahydrate:

Species : Rabbit
Result : No skin irritation

Manganese sulfate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : The test was conducted according to guideline

Copper(II) sulfate, pentahydrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Zinc sulphate monohydrate:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Sodium selenite:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : Skin irritation

Cobalt Chloride:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Calcium bis(dihydrogenorthophosphate):

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Silicon dioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Remarks : The test was conducted equivalent or similar to guideline

Ethylene diamine tetraacetic acid:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Result : Irritation to eyes, reversing within 21 days

Sodium molybdate (VI) dihydrate:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Disodium octaborate tetrahydrate:

Species : Rabbit
Result : No eye irritation

Manganese sulfate:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405
Remarks : The test was conducted according to guideline

Copper(II) sulfate, pentahydrate:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Zinc sulphate monohydrate:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Sodium selenite:

Result : Irritation to eyes, reversing within 21 days

Cobalt Chloride:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version Revision Date: SDS Number: Date of last issue: 09/22/2025
1.2 12/08/2025 11578970-00002 Date of first issue: 09/22/2025

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Calcium bis(dihydrogenorthophosphate):

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Silicon dioxide:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline

Ethylene diamine tetraacetic acid:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : The test was conducted according to guideline

Sodium molybdate (VI) dihydrate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Disodium octaborate tetrahydrate:

Test Type : Buehler Test

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Manganese sulfate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : The test was conducted equivalent or similar to guideline
Based on data from similar materials

Copper(II) sulfate, pentahydrate:

Test Type : Freund's complete adjuvant test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Zinc sulphate monohydrate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : negative
Remarks : Based on data from similar materials

Sodium selenite:

Assessment : Probability or evidence of skin sensitization in humans
Remarks : Based on national or regional regulation.

Cobalt Chloride:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of high skin sensitization rate in humans

Routes of exposure : inhalation (dust/mist/fume)
Species : Humans
Result : positive
Remarks : Based on data from similar materials

Assessment : May cause sensitization by inhalation.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Germ cell mutagenicity

Not classified based on available information.

Components:

Calcium bis(dihydrogenorthophosphate):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative
Remarks: Based on data from similar materials

Silicon dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: The test was conducted according to guideline

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 475
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Ethylene diamine tetraacetic acid:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Sodium molybdate (VI) dihydrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Disodium octaborate tetrahydrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Manganese sulfate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Copper(II) sulfate, pentahydrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: Directive 67/548/EEC, Annex V, B.12.
Result: negative

Zinc sulphate monohydrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Result: negative
Remarks: Based on data from similar materials

Sodium selenite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Cobalt Chloride:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Application Route: Intraperitoneal injection
Result: positive
Remarks: Based on data from similar materials

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Carcinogenicity

May cause cancer.

Components:

Silicon dioxide:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : No test guideline followed

Ethylene diamine tetraacetic acid:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Remarks : Based on data from similar materials

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Method : OECD Test Guideline 451
Result : negative
Remarks : The test was conducted equivalent or similar to guideline
Based on data from similar materials

Sodium molybdate (VI) dihydrate:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 106 weeks
Result : negative
Remarks : Based on data from similar materials

Disodium octaborate tetrahydrate:

Species : Mouse
Application Route : Ingestion
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Manganese sulfate:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Zinc sulphate monohydrate:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative
Remarks : Based on data from similar materials

Cobalt Chloride:

Species : Rat
Application Route : inhalation (dust/mist/fume)
Exposure time : 105 weeks
Result : positive
Remarks : Based on data from similar materials

Species : Mouse
Application Route : inhalation (dust/mist/fume)
Exposure time : 105 weeks
Result : positive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Remarks : Based on data from similar materials

Carcinogenicity - Assessment
IARC : Sufficient evidence of carcinogenicity in animal experiments
No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA : No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP : No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage fertility. May damage the unborn child.

Components:

Calcium bis(dihydrogenorthophosphate):

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Silicon dioxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: The test was conducted according to guideline

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: The test was conducted according to guideline

Ethylene diamine tetraacetic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: The test was conducted according to guideline

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: The test was conducted according to guideline

Sodium molybdate (VI) dihydrate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Disodium octaborate tetrahydrate:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Result: positive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of adverse effects on development, based on animal experiments.

Manganese sulfate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 416
Result: negative
Remarks: The test was conducted according to guideline
Based on data from similar materials

Copper(II) sulfate, pentahydrate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Zinc sulphate monohydrate:

Effects on fertility : Test Type: Fertility
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Sodium selenite:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Species: Mouse
Application Route: Ingestion
Result: negative

Cobalt Chloride:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Test Type: Fertility/early embryonic development
Species: Mouse
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

Corrosive to the respiratory tract.

STOT-repeated exposure

Causes damage to organs (Brain) through prolonged or repeated exposure.

Components:

Manganese sulfate:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Brain
Assessment : Causes damage to organs through prolonged or repeated exposure.
Remarks : Based on data from similar materials

Copper(II) sulfate, pentahydrate:

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Sodium selenite:

Routes of exposure : Ingestion
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Cobalt Chloride:

Routes of exposure : Ingestion
Target Organs : Thyroid, Heart, Blood
Assessment : Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Calcium bis(dihydrogenorthophosphate):

Species : Rat
NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407
Remarks : Based on data from similar materials

Silicon dioxide:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 26 Weeks
Method : OECD Test Guideline 408
Remarks : The test was conducted equivalent or similar to guideline

Species : Rat
NOAEL : > 2,000 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Method : OECD Test Guideline 411
Remarks : The test was conducted according to guideline

Ethylene diamine tetraacetic acid:

Species : Mouse
NOAEL : \geq 500 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Sulfuric acid, iron(2+) salt (1:1), monohydrate:

Species : Rat
LOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Remarks : Based on data from similar materials

Sodium molybdate (VI) dihydrate:

Species : Rat
NOAEL : 17 mg/kg
Application Route : Ingestion
Exposure time : 60 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Disodium octaborate tetrahydrate:

Species : Rat
NOAEL : > 10 mg/kg
LOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 2 y
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 0.2 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 10 Weeks
Remarks : Based on data from similar materials

Manganese sulfate:

Species : Rat, male
NOAEL : 200 mg/kg
Application Route : Ingestion
Exposure time : 103 Weeks

Copper(II) sulfate, pentahydrate:

Species : Rat
NOAEL : 17 mg/kg
LOAEL : 34 mg/kg
Application Route : Ingestion
Exposure time : 92 Days

Zinc sulphate monohydrate:

Species : Rat
NOAEL : 234 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Sodium selenite:

Species : Rat
NOAEL : 0.88 mg/kg
Application Route : Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Exposure time : 13 Weeks

Cobalt Chloride:

Species : Rat
LOAEL : 5.5 mg/kg
Application Route : Ingestion
Exposure time : 8 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : < 0.01 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Manganese sulfate:

Inhalation : Target Organs: Brain
Symptoms: Tremors, Lack of coordination
Remarks: Based on data from similar materials

Sodium selenite:

Inhalation : Target Organs: Respiratory Tract
Symptoms: Irritation, Edema
Target Organs: Cardio-vascular system
Symptoms: Lowered blood pressure
Target Organs: Digestive organs
Symptoms: Nausea, Vomiting, Irritability

Ingestion : Target Organs: Nervous system
Symptoms: Neurological disorders
Target Organs: Hair
Symptoms: hair loss
Target Organs: Skin
Symptoms: Rash, Skin disorders
Target Organs: Endocrine system

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Calcium bis(dihydrogenorthophosphate):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Silicon dioxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: The test was conducted according to guideline

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: The test was conducted according to guideline

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline

NOELR (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : (Daphnia magna (Water flea)): 132.7 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: The test was conducted according to guideline

Toxicity to microorganisms : NOEC (activated sludge): 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: The test was conducted according to guideline

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Ethylene diamine tetraacetic acid:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 159 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 625 mg/l
Exposure time: 24 h
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): >= 25.7 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 25 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: 2.4 mg/l
Exposure time: 24 h

Sodium molybdate (VI) dihydrate:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7,600 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 330 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 419.9 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- EC10 (Pseudokirchneriella subcapitata (green algae)): 99.3 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 17 mg/l
Exposure time: 12 Months

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 156.5 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: 820 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition of activated sludge
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Disodium octaborate tetrahydrate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 380.17 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Ceriodaphnia dubia (water flea)): 443.61 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : EC10 (Pimephales promelas (fathead minnow)): 103 mg/l
Exposure time: 32 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Hyalella azteca (Amphipod)): 31.48 mg/l
Exposure time: 42 d

Toxicity to microorganisms : NOEC (activated sludge): > 1 mg/l
Exposure time: 7 h
Remarks: Based on data from similar materials

Manganese sulfate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: No test guideline followed

Toxicity to daphnia and other aquatic invertebrates : EC50 (Hyalella azteca (Amphipod)): > 1 - 10 mg/l
Exposure time: 48 h
Remarks: No test guideline followed
Based on data from similar materials

Toxicity to algae/aquatic : EC10 (Desmodesmus subspicatus (green algae)): 13 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

- plants
- Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline
- ErC50 (Desmodesmus subspicatus (green algae)): 61 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1 mg/l
Exposure time: 65 d
Method: OECD Test Guideline 210
Remarks: The test was conducted equivalent or similar to guideline
- Toxicity to microorganisms : NOEC (activated sludge): 560 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: The test was conducted according to guideline

Copper(II) sulfate, pentahydrate:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 0.01 - 0.1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.01 - 0.1 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- NOEC (Chlamydomonas reinhardtii (green algae)): > 0.01 - 0.1 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 0.01 - 0.1 mg/l
Exposure time: 32 d
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l
Exposure time: 7 d
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: 7 mg/l

Zinc sulphate monohydrate:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

- Toxicity to fish : EC50 (Oncorhynchus mykiss (rainbow trout)): 0.384 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.192 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (fresh water algae)): 0.373 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- NOEC (Pseudokirchneriella subcapitata (green algae)): 34.5 µg/l
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): 205.2 µg/l
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 415.7 µg/l
Remarks: Based on data from similar materials
- Sodium selenite:**
- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 - 10 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.2 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Chlamydomonas reinhardtii (green algae)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- NOEC (Chlamydomonas reinhardtii (green algae)): > 0.1 - 1 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Lepomis macrochirus (Bluegill sunfish)): 0.022 mg/l
Exposure time: 258 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.096 mg/l
Exposure time: 28 d
- Toxicity to microorganisms : EC50 (activated sludge): 180 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Cobalt Chloride:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Toxicity to fish	:	LC50 (Oncorhynchus tshawytscha (chinook salmon)): 0.77 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 1.33 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Champia parvula (marine algae)): 0.053 mg/l Exposure time: 72 h EC10 (Lemna minor (common duckweed)): 0.01 mg/l Exposure time: 7 d
Toxicity to fish (Chronic toxicity)	:	NOEC (Danio rerio (zebra fish)): 0.748 mg/l Exposure time: 16 d Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC10 (Daphnia magna (Water flea)): 0.01 mg/l Exposure time: 28 d Remarks: Based on data from similar materials

Persistence and degradability

Components:

Ethylene diamine tetraacetic acid:

Biodegradability	:	Result: Inherently biodegradable. Biodegradation: 80 - 90 % Exposure time: 28 d
------------------	---	---

Bioaccumulative potential

Components:

Ethylene diamine tetraacetic acid:

Bioaccumulation	:	Species: Lepomis macrochirus (Bluegill sunfish) Bioconcentration factor (BCF): 1.8 Remarks: Based on data from similar materials
-----------------	---	--

Partition coefficient: n-octanol/water	:	log Pow: 0.13
--	---	---------------

Cobalt Chloride:

Bioaccumulation	:	Bioconcentration factor (BCF): 724
-----------------	---	------------------------------------

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper(II) sulfate, pentahydrate, Zinc sulphate monohydrate)
- Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

- UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Copper(II) sulfate, pentahydrate, Zinc sulphate monohydrate)
- Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

- UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Copper(II) sulfate, pentahydrate, Zinc sulphate monohydrate)
- Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Copper(II) sulfate, pentahydrate, Zinc sulphate monohydrate)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(Copper(II) sulfate, pentahydrate, Zinc sulphate monohydrate)
Remarks : Above applies only to containers over 119 gallons (450 liters) in case of liquids, or 882 lbs. (400 kg) in case of solids. Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters).

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Copper(II) sulfate, pentahydrate	7758-99-8	10	636
Sodium selenite	10102-18-8	100	11111
Sulfuric acid, iron(2+) salt (1:1), monohydrate	17375-41-6	1000	36363

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium selenite	10102-18-8	100	11111

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Manganese sul- 10034-96-5 >= 1 - < 5 %
fate

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

Copper(II) sulfate, pentahydrate	7758-99-8	>= 1 - < 5 %
----------------------------------	-----------	--------------

Zinc sulphate monohydrate	7446-19-7	>= 1 - < 5 %
---------------------------	-----------	--------------

US State Regulations

Pennsylvania Right To Know

Glucose	50-99-7
Diammonium hydrogenorthophosphate	7783-28-0
Calcium bis(dihydrogenorthophosphate)	7758-23-8
Protein hydrolyzates, poultry-feather	127032-53-5
Potassium chloride	7447-40-7
Ethylene diamine tetraacetic acid	60-00-4
Silicon dioxide	7631-86-9
Sulfuric acid, iron(2+) salt (1:1), monohydrate	17375-41-6
Manganese sulfate	10034-96-5
Copper(II) sulfate, pentahydrate	7758-99-8
Zinc sulphate monohydrate	7446-19-7
Sodium selenite	10102-18-8
Cobalt Chloride	7646-79-9

California List of Hazardous Substances

Ethylene diamine tetraacetic acid	60-00-4
Silicon dioxide	7631-86-9
Sulfuric acid, iron(2+) salt (1:1), monohydrate	17375-41-6
Sodium molybdate (VI) dihydrate	10102-40-6
Manganese sulfate	10034-96-5
Copper(II) sulfate, pentahydrate	7758-99-8
Zinc sulphate monohydrate	7446-19-7

California Permissible Exposure Limits for Chemical Contaminants

Silicon dioxide	7631-86-9
Sulfuric acid, iron(2+) salt (1:1), monohydrate	17375-41-6
Sodium molybdate (VI) dihydrate	10102-40-6
Manganese sulfate	10034-96-5
Copper(II) sulfate, pentahydrate	7758-99-8

The ingredients of this product are reported in the following inventories:

AICS	: not determined
CA. DSL	: not determined
IECSC	: not determined

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET


according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version 1.2 Revision Date: 12/08/2025 SDS Number: 11578970-00002 Date of last issue: 09/22/2025
Date of first issue: 09/22/2025

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CAL PEL	:	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organiza-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Metal Sulfates Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 09/22/2025
1.2	12/08/2025	11578970-00002	Date of first issue: 09/22/2025

tion; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/08/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8