

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

SECTION 1. IDENTIFICATION

Product name : Vorinostat Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Pharmaceutical
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Germ cell mutagenicity : Category 2
Reproductive toxicity : Category 1B
Specific target organ toxicity : Category 1 (Blood, thymus gland, Bone marrow, spleen, Gastro-intestinal tract)
- repeated exposure (Oral)

Other hazards

Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.

Hazards associated with a change in physical form:

Conditions	Hazards
If small particles are generated during further processing, handling or by other means.	May form combustible dust concentrations in air.

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H341 Suspected of causing genetic defects.
H360FD May damage fertility. May damage the unborn child.
H372 Causes damage to organs (Blood, thymus gland, Bone marrow, spleen, Gastrointestinal tract) through prolonged or repeated exposure if swallowed.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:
P308 + P313 IF exposed or concerned: Get medical attention.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Vorinostat	149647-78-9*	>= 60 - <= 80	TSC
Cellulose	9004-34-6*	>= 10 - <= 30	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : If in eyes, rinse well with water.
Get medical attention if irritation develops and persists.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
 - Most important symptoms and effects, both acute and delayed : Suspected of causing genetic defects.
May damage fertility. May damage the unborn child.
Causes damage to organs through prolonged or repeated exposure if swallowed.
Contact with dust can cause mechanical irritation or drying of the skin.
Dust contact with the eyes can lead to mechanical irritation.
No information available.
 - Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
 - Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
 - Unsuitable extinguishing media : None known.
 - Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Exposure to combustion products may be a hazard to health.
 - Hazardous combustion products : Carbon oxides
Metal oxides
 - Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
 - Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe dust.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust	50 Million particles per cubic foot Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	15 mg/m ³ Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	5 mg/m ³ Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
	15 Million particles per cubic foot Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
Dust, nuisance dust and particulates	10 mg/m ³ Value type (Form of exposure): PEL (Total dust) Basis: CAL PEL
	5 mg/m ³ Value type (Form of exposure): PEL (respirable dust fraction) Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Vorinostat	149647-78-9	TWA	5 µg/m ³	Internal
		Wipe limit	50 µg/100 cm ²	Internal
Cellulose	9004-34-6	TWA	10 mg/m ³	ACGIH
		TWA (Respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1

Engineering measures : Minimize workplace exposure concentrations.
Apply measures to prevent dust explosions.
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	42862-00023	Date of first issue: 01/06/2015

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	No data available
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	42862-00023	Date of first issue: 01/06/2015

Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	May form explosive dust-air mixture during processing, handling or other means.
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	May form explosive dust-air mixture during processing, handling or other means. Can react with strong oxidizing agents.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	42862-00023	Date of first issue: 01/06/2015

Conditions to avoid : Heat, flames and sparks.
Avoid dust formation.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: 3,788 mg/kg
Method: Calculation method

Components:

Vorinostat:

Acute oral toxicity : LD50 (Mouse): > 2,000 mg/kg
LD50 (Rat): > 750 mg/kg

Acute toxicity (other routes of administration) : LDLo (Mouse): 1,250 mg/kg
Application Route: Intravenous
Exposure time: 4 h

Cellulose:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Vorinostat:

Species : Rabbit
Result : No skin irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Vorinostat:

Species : Bovine cornea
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Vorinostat:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Result : Not a skin sensitizer.

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Vorinostat:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Result: positive

Test Type: Chromosome aberration test in vitro
Test system: Human lymphocytes
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Oral
Result: positive

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Cellulose:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Genotoxicity in vivo : Result: negative
Test Type: In vitro mammalian cell gene mutation test
Result: negative
: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Cellulose:

Species : Rat
Application Route : Ingestion
Exposure time : 72 weeks
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage fertility. May damage the unborn child.

Components:

Vorinostat:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat, female
Application Route: Oral
Fertility: LOAEL: 15 mg/kg body weight
Result: Preimplantation loss., Increased resorptions.

Test Type: Fertility/early embryonic development
Species: Rat, male
Application Route: Oral
Fertility: NOAEL: 150 mg/kg body weight
Result: No effects on fertility.

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Oral
Developmental Toxicity: LOAEL: 50 mg/kg body weight

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Result: positive

Test Type: Embryo-fetal development
Species: Rat
Application Route: Oral
Developmental Toxicity: NOAEL: 15 mg/kg body weight
Result: positive

Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Oral
Developmental Toxicity: LOAEL: 150 mg/kg body weight
Result: Embryotoxic effects.

Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Oral
Developmental Toxicity: NOAEL: 50 mg/kg body weight
Result: Embryotoxic effects.

Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Oral
Developmental Toxicity: LOAEL: 15 mg/kg body weight
Result: Malformations were observed.

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of adverse effects on development, based on animal experiments.

Cellulose:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Blood, thymus gland, Bone marrow, spleen, Gastrointestinal tract) through prolonged or repeated exposure if swallowed.

Components:

Vorinostat:

Routes of exposure : Ingestion

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Target Organs : Blood, thymus gland, Bone marrow, spleen, Gastrointestinal tract
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Vorinostat:

Species : Rat
LOAEL : 20 mg/kg
Application Route : Oral
Exposure time : 6 Months
Target Organs : Blood, thymus gland, Bone marrow, spleen

Species : Dog
NOAEL : 60 mg/kg
LOAEL : 160 mg/kg
Application Route : Oral
Exposure time : 6 Months
Target Organs : Gastrointestinal tract

Species : Dog
NOAEL : 40 mg/kg
LOAEL : 100 mg/kg
Application Route : Oral
Exposure time : 4 Weeks
Target Organs : Blood

Cellulose:

Species : Rat
NOAEL : $\geq 9,000$ mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Vorinostat:

Ingestion : Symptoms: Diarrhea, Fatigue, Nausea, anorexia

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Vorinostat:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 10 mg/l Exposure time: 96 h LC50 (Cyprinodon variegatus (sheepshead minnow)): > 10 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10 mg/l Exposure time: 48 h EC50 (Americamysis): 7.4 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 0.183 mg/l Exposure time: 96 h Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 0.011 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Pimephales promelas (fathead minnow)): 1.5 mg/l Exposure time: 33 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.15 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	: EC50: > 1,000 mg/l Exposure time: 3 h Test Type: Respiration inhibition

Cellulose:

Toxicity to fish	: LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
------------------	--

Persistence and degradability

Components:

Vorinostat:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 39.5 % Exposure time: 28 d Method: OECD Test Guideline 314
------------------	--

Cellulose:

Biodegradability	: Result: Readily biodegradable.
------------------	----------------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

II

Bioaccumulative potential

Components:

Vorinostat:

|| Partition coefficient: n- : log Pow: 1.42
|| octanol/water

Mobility in soil

Components:

Vorinostat:

|| Distribution among environ- : log Koc: 3.37
|| mental compartments

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Vorinostat)

|| Class : 9
|| Packing group : III
|| Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Vorinostat)

|| Class : 9
|| Packing group : III
|| Labels : Miscellaneous
Packing instruction (cargo : 956
aircraft)
Packing instruction (passen- : 956
ger aircraft)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Vorinostat)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Vorinostat)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(Vorinostat)
Remarks : Above applies only to containers over 119 gallons (450 liters) in case of liquids, or 882 lbs. (400 kg) in case of solids. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Germ cell mutagenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version 9.0 Revision Date: 12/06/2025 SDS Number: 42862-00023 Date of last issue: 04/14/2025
Date of first issue: 01/06/2015

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Vorinostat 149647-78-9
Cellulose 9004-34-6
Croscarmellose sodium 74811-65-7

California Permissible Exposure Limits for Chemical Contaminants

Cellulose 9004-34-6


The ingredients of this product are reported in the following inventories:

AICS : not determined
CA. DSL : not determined
IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CAL PEL : California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	42862-00023	Date of first issue: 01/06/2015

OSHA Z-3	:	its for Air Contaminants USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/06/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Vorinostat Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/14/2025
9.0	12/06/2025	42862-00023	Date of first issue: 01/06/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8